

OsmoSGSN - Bug #3922

lu: send RANAP CommonID to known connection

04/13/2019 02:21 AM - lynxis

Status: Closed	Start date: 04/13/2019
Priority: Normal	Due date:
Assignee:	% Done: 100%
Category: lu interface	
Target version:	
Spec Reference:	
Description An RNC can be a unique reference number told (usually the IMSI) to recognize connection across CS/PS. The RNC can use this information to send paging requests over a present connection. CommonID should be send as soon an connection is identified e.g. RAU / Attach Request. As soon a SecurityCommand Complete has been validated, the IMSI can be sent. OS#3920 has a trace where this is happening.	
Related issues: Related to OsmoSGSN - Support #3920: PCAPs files of 3G PS for Osmocom network... In Progress 04/12/2019	

History

#1 - 04/14/2019 02:10 AM - lynxis

- Subject changed from send RANAP CommonID to known connection to lu: send RANAP CommonID to known connection

#2 - 04/14/2019 02:10 AM - lynxis

- Category set to lu interface

#3 - 04/16/2019 06:59 PM - lynxis

- Related to Support #3920: PCAPs files of 3G PS for Osmocom network and Commercial one added

#4 - 04/24/2019 08:26 AM - laforge

- Checklist item [] ttcn-3 test case for it added

note: We do send CommonID on luCS from OsmoMSC.

#5 - 09/16/2019 07:40 PM - lynxis

- Checklist item [x] ttcn-3 test case for it set to Done

#6 - 09/16/2019 07:41 PM - lynxis

- Status changed from New to Closed

- % Done changed from 0 to 100

CommonID is required by RAU and GMM Attach procedure in TTCN3 as well the patch for the SGSN has been merged.